



MAXIM BALLISTIC TAC PACK

Clear / Amber / Bronze lens with case



FRAME

- Plastic frame with DuoForm mould processing
- Dual injected cushion browguard
- Soft universal-fit nose bridge pivots
- Ventilation channel on the top
- Flat temples with pantoscopic adjustment to wear under ear muff and helmet
- Easy lens replacement system by removing the temples (rotation to the top)
- Soft case with belt loop to fit 3 Maxim lenses

LENS

- Polycarbonate patented aspherical lens: (better coverage and perfect field of vision)
- Optical quality class 1 (no distortion)
- Resistance to impact (45m/s)
- 100% UV filtration (in conformity with EN 170)
- DX coating : anti-fog, anti-scratch, anti-static and anti-chemical attack
- Visible Light Transmittance = 92% (Clear) / 94% (Amber) / 20% (Bronze)

FIELDS OF USE

- Shooting (3 different filter types)
- Mechanical hazards (marking F - 45m/s)
- UV radiation (accidental electric arc)
- Mist
- Clear lens : indoor
- Amber lens : low light condition (cloudy env.)
- Bronze lens : sunny condition

DO NOT USE FOR

Does not protect against liquid, dust, molten metal, laser beam, or any kind of welding application

FRAME MARKING

AOS EN166 - F CE

AOS = manufacturer Aearo
 EN166 = n° of the standard
 F = impact resistance (45m/s)
 CE = conformity marking

EUROPEAN STANDARD

This product conforms to the European Council Directive 89/686/EEC and with the EN166 : 2001

EC-Type Examination Certificate n° 1202

Issued by INSPEC (notified body n°0194), Upper Wingbury Courtyard, Wingrave, Aylesbury, Buckinghamshire, HP22LW, England

Conform to EN166 - EN170 - EN172

LENS MARKING

2-1,2 . AOS . 1 . F (Clear & Amber)

5-2,5 . AOS . 1 . F (Bronze)

2 = UV filter (EN 170) 5 = solar filter (EN172)
 1,2 = shade number - Clear & Amber
 2,5 = shade number - Bronze (brown-yellow tint)
 AOS = manufacturer Aearo
 1 = optical class (permanent wear)
 F = impact resistance (45m/s)

PRODUCT REFERENCE

Product Code	Frame	Lens	Material
13200-00000			PC anti-fog DX